

THE JAMES WALKER CO.

CROSBY WIRELOCK

RESIN FOR SPELTER SOCKETS NOT AVAILABLE IN CANADA

Note: For use on 416, 417, 427 and 517 spelter sockets only.

- 100% termination efficiency.
- Temperature operating range is -65° F to +240° F.
- Ideal for on site applications.
- No hazardous molten metal.
- Improved fatigue life.
- Pouring temperature without booster pack is 48° F to 110° F.
- One booster pack if pouring temperature is 35° F to 48° F.
- Two booster packs if pouring temperature is 27° F to 35° F.
- Refer to WIRELOCK® Technical Manual for more information.



Approvals

Lloyds Register of Shipping
Det Norske Veritas (DNV)
United States Coast Guard
Registro Italiano Navale
Germanischer Lloyd
United States Navy
American Bureau of Shipping.



U.S. Department
of Transportation
United States
Coast Guard



WIRELOCK® W416-7 Socket Compound

W416-7 Kits				Booster Pack
Kit Size	Kit Per Case	Stock No.	Weight Each (lbs.)	Stock No.
100	20	1039602	.62	1039603
250	12	1039604	1.25	1039605
500	12	1039606	2.54	1039607
1000	12	1039608	4.59	1039609
2000	12	1039610	9.00	1039611

Guide to amount WIRELOCK® Required

Wire Rope Size		WIRELOCK® Required (cc)	Wire Rope Size		WIRELOCK® (cc)
(in.)	(mm)		(in.)	(mm)	
1/4	6-7	9	1-3/4	44	700
5/16	8	17	1-7/8	48	700
3/8	9-10	17	2	51	1265
7/16	11	35	2-1/8	54	1265
1/2	13	35	2-1/4	56	1410
9/16	14	52	2-3/8	60	1410
5/8	16	52	2-1/2	64	1830
3/4	20	86	2-5/8	67	1830
7/8	22	125	2-3/4	70	2250
1	26	160	3	76	3160
1-1/8	28	210	3-1/4	82	3795
1-1/4	32	350	3-1/2	88	4920
1-3/8	36	350	3-3/4	94	5980
1-1/2	40	420	4	102	7730
1-5/8	42	495	—	—	—

NATO Numbers:

100cc 8030-21-902-1823
250cc 8030-21-902-1824
500cc 8030-21-902-1825
1000cc 8030-21-902-1826

Witnessed and tested by American Bureau of Shipping. (ABS)

Approximate U.S. Measurements:

250cc's Kit 1 Cup
500cc's Kit 1 Pint
1000cc's Kit 1 Quart

The hazardous material/dangerous good classification under U.S. DOT, ICAO/IATA and IMO transportation regulations is Resin Solution, flammable liquid class 3, UN1866, packing group III. All shipments made by The Crosby Group, Inc. are under limited quantity packing provisions.

WARNING: DO NOT EXCEED RATED CAPACITIES