

# THE JAMES WALKER CO.

## PEERLESS CARBON CHAIN

### Specifications

Trade Size	Nominal Wire Dia. Inches	Nominal Inside Length Inches	Minimum Inside Width Inches	WLL Lbs.	Weight Per 100 Feet Lbs.
<b>Proof Coil (P3/P30) Grade 30</b>					
3/16" (5.5 mm)	0.217	0.950	0.405	800	40
1/4" (7 mm)	0.274	1.236	0.480	1,300	63.5
5/16" (8 mm)	0.328	1.285	0.480	1,900	93
3/8" (10 mm)	0.392	1.374	0.551	2,650	136
1/2" (13 mm)	0.509	1.782	0.750	4,500	230
5/8"	0.625	2.016	0.851	6,900	369
3/4"	0.781	2.610	1.020	10,600	533
7/8"	0.904	2.570	1.260	12,800	775
1"	1.032	2.900	1.435	17,900	1010
<b>High Test (P4/P43) Grade 43</b>					
1/4" (7 mm)	0.274	1.236	0.480	2,600	63.5
5/16" (8 mm)	0.328	1.285	0.480	3,900	93
3/8" (10 mm)	0.392	1.374	0.551	5,400	136
1/2" (13 mm)	0.509	1.782	0.750	9,200	230
5/8"	0.625	2.016	0.851	13,000	369
3/4"	0.781	2.610	1.020	20,200	533
7/8"	0.904	2.570	1.260	24,500	775
1"	1.032	2.870	1.420	26,000	1010
<b>Transport (P7/P70) Grade 70</b>					
1/4" (7 mm)	0.274	1.236	0.480	3,150	63.5
5/16" (8 mm)	0.334	1.120	0.480	4,700	100
3/8" (10 mm)	0.392	1.374	0.551	6,600	136
11.9 mm	0.467	1.620	0.660	8,750	201
1/2" (13 mm)	0.510	1.782	0.750	11,300	230
5/8"	0.625	2.016	0.851	15,800	347

**WARNING: DO NOT EXCEED RATED CAPACITIES**