


# THE JAMES WALKER CO.

## CROSBY FORGED HOOKS

### BH-313



- Wide range of sizes available: 1-10 Metric Ton capacity.
- Forged Alloy Steel.
- Designed for attachment to mobile lifting equipment to provide a pick point for easy sling attachment.
- Large weld pad.
- Heavy duty latch interlocks with the hook tip. Replacement latches available.
- Detailed installation and application instructions included with each hook.



### BH-313 Weld-On Hooks


Working Load Limit (t)*	BH-313 Stock No.	Weight Each (lbs.)	Dimensions (in.)								Replacement Latch Stock No.
			B	E	F	G	H	J	K	S	
1	1029105	1.15	.91	3.82	2.80	1.42	1.06	1.02	4.21	.71	1092101
2	1029114	1.85	.91	3.23	3.58	1.42	.98	1.34	4.53	.83	1092101
3	1029123	2.60	1.14	4.61	4.13	1.42	1.22	1.42	5.16	.94	1092101
4	1029132	4.19	1.34	5.16	4.49	1.81	1.42	1.69	5.79	1.14	1092102
5	1029141	5.62	1.34	6.34	5.24	1.85	1.77	1.73	6.81	1.14	1092102
8	1029150	7.28	1.38	6.54	5.31	1.85	2.05	2.05	7.01	1.54	1092102
10	1029169	11.02	1.93	8.07	6.61	1.85	2.24	2.13	8.74	1.54	1092103

\* Ultimate Load is 5 times the Working Load Limit.

### A-350N



- New style incorporates throat opening equal to or larger than old style hooks.
- Each product has a Product Identification Code (PIC) for material traceability, along with a Working Load Limit, and the name Crosby or "CG" forged into it.
- All hooks incorporate Crosby's patented **QUIC-CHECK®** marks to help in determining if throat opening dimension has changed.
- Each hook can be equipped with a Crosby S-4320 heavy duty stamped latch with the high cycle, long life spring.
- Forged Alloy Steel – Quenched and Tempered.
- Design Factor of 5 to 1



### A-350N Sliding Choker Hook

Single Part Rope Size (in.)	Eight Part Rope Size (in.)	A-350N Stock No.	Working Load Limit (lbs.)*	Weight Each (lbs.)	Dimensions (in.)											Hook Frame Code	Replacement Latch Kit Stock No.
					A	B	C	D	E	F	G	H	L	P	R		
3/8	-	1011707	2500	1.0	2.06	1.13	.63	2.41	.63	.38	.84	.91	4.28	2.59	.63	D	1096325
1/2	1/8	1011716	3800	1.4	2.25	1.31	.75	2.97	.78	.50	.97	1.06	4.97	3.09	.75	D	1096325
† 5/8	-	1011725	5800	3.0	3.06	1.63	.75	3.56	.94	.56	1.13	1.31	6.38	3.88	1.00	G	1096421
† 5/8	3/16	1011734	5800	2.7	3.06	1.63	1.00	3.56	.94	.56	1.13	1.31	6.38	4.00	1.13	G	1096421
† 3/4	-	1011743	8200	4.4	3.38	2.13	1.00	4.25	1.16	.63	1.44	1.63	7.66	4.58	1.13	H	1096468
† 3/4	1/4	1011752	8200	3.8	3.38	2.13	1.44	4.25	1.16	.63	1.44	1.63	7.66	4.78	1.13	H	1096468
†† 7/8-1	-	1028177	15000	9.70	4.41	2.12	1.25	6.06	1.41	.88	2.00	2.33	9.55	5.72	1.50	I	1096515

\* Ultimate Load is 5 times the Working Load Limit.  
 † Determine EYE diameter "C", before ordering.  
 †† 7/8-1" is Cast Steel & furnished with latch attached.

**WARNING: DO NOT EXCEED RATED CAPACITIES**