


# THE JAMES WALKER CO.


## STAINLESS STEEL HARDWARE

<b>ANCHOR SHACKLE</b>		<b>ITEM</b>	<b>A</b>	<b>B</b>	<b>C</b>	<b>D</b>	<b>WLL</b>	<b>WT</b>
	<b>316-NM STAINLESS STEEL WITH OVERSIZE SCREW PIN</b>	(size)					(lb)	(lb)
		S0116-FS05	3/16"	0.26"	0.41"	0.83"	650	0.05
		S0116-FS07	1/4"	0.31"	0.47"	1.11"	1,000	0.10
		S0116-FS08	5/16"	0.38"	0.53"	1.20"	1,300	0.17
		S0116-FS10	3/8"	0.44"	0.66"	1.41"	1,500	0.30
		S0116-FS12	7/16"	0.50"	0.72"	1.77"	2,000	0.50
		S0116-FS13	1/2"	0.63"	0.82"	1.83"	3,000	0.71
		S0116-FS16	5/8"	0.75"	1.02"	2.41"	4,000	1.39
		S0116-FS20	3/4"	0.88"	1.25"	2.84"	6,000	2.31
		S0116-FS22	7/8"	1.00"	1.48"	3.30"	8,000	3.64
		S0116-FS25	1"	1.13"	1.70"	3.80"	10,000	5.18
		S0116-FS32	1-1/4"	1.38"	2.03"	4.69"	14,000	9.88


**NOTE: I/A/W FED SPEC RR-C-271D, TYPE IVA, CLASS 2, EXCEPT 316 STAINLESS.**

<b>NITRONIC ANCHOR SHACKLE</b>		<b>ITEM</b>	<b>A</b>	<b>B</b>	<b>C</b>	<b>D</b>	<b>WLL</b>	<b>WT</b>
	<b>NITRONIC 50™ WITH OVERSIZE SCREW PIN</b>	(size)					(lb)	(lb)
		S0116-NM07	1/4"	0.33"	0.49"	1.09"	1,500	0.12
		S0116-NM10	3/8"	0.44"	0.66"	1.41"	2,000	0.30
		S0116-NM13	1/2"	0.63"	0.82"	1.83"	4,000	0.71
		S0116-NM16	5/8"	0.75"	1.02"	2.41"	6,000	1.39
		S0116-NM20	3/4"	0.87"	1.25"	2.84"	10,000	2.31
		S0116-NM22	7/8"	0.98"	1.54"	3.35"	12,000	3.62
		S0116-NM25	1"	1.14"	1.72"	3.76"	16,000	5.17


**NOTE: I/A/W MIL-F-17280D, TYPE 1. USED BY THE U.S. NAVY FOR MINESWEEPING. NITRONIC EYE & EYE SWIVEL, I/A/W MIL-F-17280D TYPE III, STYLE A, IS SHOWN IN RIGGING, PAGE 58.**

<b>BOLT ANCHOR SHACKLE</b>		<b>ITEM</b>	<b>A</b>	<b>B</b>	<b>C</b>	<b>D</b>	<b>WLL</b>	<b>WT</b>
	<b>316-NM STAINLESS STEEL WITH OVERSIZE BOLT</b>	(size)					(lb)	(lb)
		S0116-SA07	1/4"	0.31"	0.47"	1.11"	1,000	0.12
		S0116-SA08	5/16"	0.38"	0.53"	1.20"	1,300	0.18
		S0116-SA10	3/8"	0.44"	0.66"	1.41"	1,500	0.35
		S0116-SA12	7/16"	0.50"	0.72"	1.77"	2,000	0.57
		S0116-SA13	1/2"	0.63"	0.82"	1.83"	3,000	0.84
		S0116-SA16	5/8"	0.75"	1.02"	2.41"	4,000	1.64
		S0116-SA20	3/4"	0.88"	1.25"	2.84"	6,000	2.75
		S0116-SA22	7/8"	1.00"	1.48"	3.30"	8,000	4.18
		S0116-SA25	1"	1.13"	1.70"	3.80"	10,000	5.61
		S0116-SA32	1-1/4"	1.38"	2.03"	4.69"	14,000	9.88

**NOTE: I/A/W FED SPEC RR-C-271D, TYPE IVA, CLASS 3, EXCEPT 316 STAINLESS. OTHER SIZES AVAILABLE ON SPECIAL ORDER.**

<b>ANCHOR SHACKLE</b>		<b>ITEM</b>	<b>A</b>	<b>B</b>	<b>C</b>	<b>D</b>	<b>WLL</b>	<b>WT</b>
	<b>316-NM STAINLESS STEEL WITH OVERSIZE ROUND PIN</b>	(size)					(lb)	(lb)
		S0116-RP07	1/4"	0.31"	0.47"	1.11"	1,000	0.10
		S0116-RP08	5/16"	0.38"	0.53"	1.20"	1,300	0.17
		S0116-RP10	3/8"	0.44"	0.66"	1.41"	1,500	0.32
		S0116-RP12	7/16"	0.50"	0.72"	1.77"	2,000	0.49
		S0116-RP13	1/2"	0.63"	0.82"	1.83"	3,000	0.72
		S0116-RP16	5/8"	0.75"	1.02"	2.41"	4,000	1.53
		S0116-RP20	3/4"	0.88"	1.25"	2.84"	6,000	2.36
		S0116-RP22	7/8"	1.00"	1.48"	3.30"	8,000	4.00
		S0116-RP25	1"	1.13"	1.70"	3.80"	10,000	5.27
		S0116-RP32	1-1/4"	1.38"	2.03"	4.69"	14,000	9.88

**NOTE: I/A/W FEDERAL SPECIFICATION RR-C-271D, TYPE IVA, CLASS 1, EXCEPT 316 STAINLESS.**

<b>US ANCHOR SHACKLE</b>		<b>ITEM</b>	<b>A</b>	<b>B</b>	<b>C</b>	<b>D</b>	<b>WLL</b>	<b>WT</b>
	<b>316-NM STAINLESS STEEL WITH OVERSIZE SCREW PIN</b>	(size)					(lb)	(lb)
		S0116-US07	1/4"	0.31"	0.47"	1.11"	1,000	0.10
		S0116-US08	5/16"	0.38"	0.53"	1.20"	1,300	0.17
		S0116-US10	3/8"	0.44"	0.66"	1.41"	1,500	0.30
		S0116-US12	7/16"	0.50"	0.72"	1.77"	2,000	0.50
		S0116-US13	1/2"	0.63"	0.82"	1.83"	3,000	0.71
		S0116-US16	5/8"	0.75"	1.02"	2.41"	4,000	1.39
		S0116-US20	3/4"	0.88"	1.25"	2.84"	6,000	2.31
		S0116-US22	7/8"	1.00"	1.48"	3.30"	8,000	3.64
		S0116-US25	1"	1.13"	1.70"	3.80"	10,000	5.18

**NOTE: I/A/W FED SPEC RR-C-271D, TYPE IVA, CLASS 2, EXCEPT 316 STAINLESS. MEETS ASME B30.26-2004 AMERICAN NATIONAL STANDARD. DFARS COMPLIANT SHACKLES.**

**WARNING: DO NOT EXCEED RATED CAPACITIES**