










# THE JAMES WALKER CO.



## STAINLESS STEEL HARDWARE

<b>EYE &amp; EYE SWIVEL</b>		<b>ITEM</b>	<b>A</b>	<b>B</b>	<b>C</b>	<b>D</b>	<b>WLL</b>	<b>WT</b>
		<b>316 STAINLESS STEEL</b>		(size)			(lb)	(lb)
		S0128-0004	5/32"	0.43"	0.50"	2.00"	150	0.12
		S0128-0005	3/16"	0.50"	0.50"	2.31"	300	0.12
		S0128-0006	1/4"	0.56"	0.56"	2.56"	600	0.12
		S0128-0008	5/16"	0.75"	0.75"	3.62"	1,100	0.29
		S0128-0010	3/8"	0.87"	1.00"	4.39"	1,540	0.55
		S0128-0013	1/2"	1.25"	1.31"	6.00"	2,640	1.25
		S0128-0016	5/8"	1.50"	1.62"	7.37"	4,750	2.10
		S0128-0020	3/4"	1.62"	2.00"	8.50"	7,000	3.40
		S0128-0022	7/8"	1.87"	2.00"	9.25"	8,000	5.02
		S0128-0025	1"	2.50"	2.56"	11.00"	10,000	8.73
		<b>NITRONIC - FORGED</b>						
		S0128-NM10	3/8"	1.25"	1.31"	4.13"	3,000	0.70

<b>HEAVY DUTY EYE &amp; EYE SWIVEL</b>		<b>ITEM</b>	<b>A</b>	<b>B</b>	<b>C</b>	<b>D</b>	<b>WLL</b>	<b>WT</b>
		<b>316 STAINLESS STEEL</b>		(size)			(lb)	(lb)
		S0128-HD07	1/4"	0.50"	0.68"	3.25"	750	0.27
		S0128-HD08	5/16"	0.62"	0.87"	3.62"	1,400	0.52
		S0128-HD10	3/8"	0.75"	1.00"	4.62"	2,000	0.88
		S0128-HD13	1/2"	1.00"	1.37"	6.00"	3,300	2.00
		<b>NOTE: MARKED WITH SIZE AND WORKING LOAD.</b>						
								

<b>NITRONIC EYE &amp; EYE SWIVEL</b>		<b>ITEM</b>	<b>A</b>	<b>B</b>	<b>C</b>	<b>D</b>	<b>WLL</b>	<b>WT</b>
		<b>NITRONIC 50</b>		(size)			(lb)	(lb)
		S0128-NM10	3/8"	1.25"	1.31"	4.13"	3,000	0.70
		<b>NOTE: I/A/W MIL-F-17280D TYPE III, STYLE A. NITRONIC SHACKLES ARE SHOWN ON PAGE 7.</b>						

<b>EYE &amp; JAW SWIVEL</b>		<b>ITEM</b>	<b>A</b>	<b>B</b>	<b>C</b>	<b>D</b>	<b>WLL</b>	<b>WT</b>
		<b>316 STAINLESS STEEL</b>		(size)			(lb)	(lb)
		S0155-0006	1/4"	0.50"	0.43"	2.62"	600	0.14
		S0155-0008	5/16"	0.62"	0.62"	3.62"	1,100	0.33
		S0155-0010	3/8"	0.75"	0.87"	4.35"	1,540	0.63
		S0155-0013	1/2"	1.00"	1.12"	6.00"	2,640	1.40
		S0155-0016	5/8"	1.25"	1.37"	7.37"	4,750	2.36
		S0155-0020	3/4"	1.50"	1.62"	8.62"	7,000	3.93
		<b>NOTE: SUNCOR RECOMMENDS THE USE OF THREAD LOCKING FLUID WITH THIS TYPE OF SWIVEL.</b>						

<b>EYE &amp; JAW SWIVEL</b>		<b>ITEM</b>	<b>A</b>	<b>B</b>	<b>C</b>	<b>D</b>	<b>WLL</b>	<b>WT</b>
		<b>316 STAINLESS STEEL W/ NO SNAG PIN</b>		(size)			(lb)	(lb)
		S0155-NS06	1/4"	0.50"	0.43"	2.62"	600	0.14
		<b>NOTE: NO SNAG SHACKLE PIN SITS FLUSH WITH BODY OF SWIVEL. SUNCOR RECOMMENDS USING THREAD LOCKING FLUID WITH THIS TYPE OF SWIVEL.</b>						

**WARNING: DO NOT EXCEED RATED CAPACITIES**