

# THE JAMES WALKER CO.

## McKISSICK SNATCH BLOCKS

### 420, 421 & 406 SNATCH BLOCKS



**420  
WITH HOOK**



**421  
WITH SHACKLE**



**T-350-C**

### Champion

- Hooks and side plates are forged alloy steel and heat treated.
- Shackles and yokes are forged and heat treated steel.
- All parts are forged.
- Side plates are designed to eliminate possibility of rope jamming.
- Can be furnished with bronze bushings or sealed roller bearings.
- Opening feature permits insertion of rope while block is suspended from gin-pole.
- Can be furnished with S-4320 hook latch.
- Pressure lube fittings.
- Hook and shackle assemblies can be interchanged.
- Blocks furnished with dual rated wireline sheaves.
- Fatigue Rated.
- All sizes are **RFID EQUIPPED**.



Sheave Diam. (in.)	Bearing Code	Stock No.			Wire Rope Size (in.) †	Working Load Limit (t) †	Weight Each (lbs.)			Rep. Sheave Stock No.	Rep. Latch Stock No.
		420 with Hook	421 with Shackle	406 Tail Board			420 with Hook	421 with Shackle	406 Tail Board		
6	BB	169374	169481	167973	3/4 - 7/8	12	40	48	24	460940	1096609
6	RB	169392	204120	167982	3/4 - 7/8	12	40	48	24	473035	1096609
8	BB	169418	169515	167991	3/4 - 7/8	15	51	57	30	461360	1096609
8	RB	169445	204193	168008	3/4 - 7/8	15	51	57	30	473534	1096609
10	BB	110221	110720	103186	3/4 - 7/8	15	63	69	42	462001	1096609
10	RB	110258	110757	103202	3/4 - 7/8	15	63	69	42	474025	1096609

\* Ultimate Load is 4 times the Working Load Limit.  
† May be furnished in other Wire Rope sizes.

NOTE: When ordering, please specify: size, block number, hook or shackle, bronze bushed or roller bearing, and wire rope size.

### Gin Blocks for Manila Rope

- For light hoisting by Roofers and Contractors.
- Furnished with drop forged swivel latch hooks.

Block Size (in.)	Fitting	Gin Block Stock No.			Sheave Size (in.)			Manila Rope Size (in.)	Working Load Limit (lbs.)*	Weight Each (lbs.)
		T-350-B	T-350-R	T-350-C	Outside Diam.	Rim Thickness	Bearing Diam.			
8	T	710403	710207	710001	8.00	1.25	.75	7/8	1000	9.0
10	T	710421	710225	710029	10.00	1.25	.88	1	1000	9.8
12	T	710449	710243	710047	12.00	1.38	.88	1	1000	12.7

\* Ultimate Load is 3 times the Working Load Limit.

Bearing Code: B-Self Lubricating Bronze Bushed, R-Roller Bearing, C-Common Iron

**WARNING: DO NOT EXCEED RATED CAPACITIES**